

MATERIAL SAFETY DATA SHEET

Rev. 01/23/2007

AQUA- FLUX

ALLIED RUBBER & GASKET CO.
2610 COMMERCE WAY
VISTA, CA 92081

Phone: 800-854-1015
Infotrac Emergency No. 1-800-535-5053

1. PRODUCT INGREDIENTS

<u>Chemical Name</u>	<u>CAS No.</u>	<u>PEL</u>	<u>Hazard</u>
Ammonium Chloride	12125-02-9	10mg/m ²	ACGIH
Glycerine	56-81-5	10mg/m ²	ACGIH
Hydrobromic Acid	7664-38-2	1.0mg/m ¹	ACGIH

Remaining ingredients, if any, are classified and claimed as trade secret.

N/A – Not Applicable

N/A – Not Established

2. PHYSICAL DATA

Material is
SEMI-SOLID

Appearance and Odor
OPAGUE WHITE TO YELLOWISH – NO ODOR

Boiling Point
N/E

Specific Gravity
1.014

Vapor Density
N/E

Vapor Pressure
n/e

Solubility in Water
APPRECIABLE

Evaporation Rate
<1

% Volatile
N/E

3. FIRE AND EXPLOSION DATA

Flash Point
N/A

Flammable Limits
N/A

Extinguishing Media-
Water or foam

Special Fire Fighting Procedures-
Full protective equipment required. May release ammonia and HCl fumes. Toxic metal halide fumes produced.

Unusual Fire and Explosion Hazards-
Dense smoke may be generated.

4. HEALTH HAZARD INFORMATION

Target Organ Statement:

WARNING: Causes burns to skin, eyes and respiratory system. MAY BE FATAL IF SWALLOWED OR INHALED.

Effects of Chronic Exposure:

Irritation to skin (scarring), eyes and respiratory system. Possible liver and kidney effects.

Effects of Acute Overexposure:

Swallowing-can cause damage to digestive system. Corrosive to mucous membranes.

Skin Absorption-None currently known.

Inhalation-Irritation to respiratory system. Coughing and sneezing. Existing lung disorders will be aggravated.

Skin Contact-Dermatitis, possible chemical burns, corrosive to skin. Existing disorders will be aggravated.

Eye Contact-Irritation to eyes, tearing, burn of eye surfaces, corrosive to eyes. **MAY CAUSE BLINDNESS.**

5. FIRST AID PROCEDURES

Swallowing-

Call a physician at once or your Poison Control Center. Corrosive to mucous membranes.

Skin-

Promptly flush with water to remove all residues. If rash or burn develops, consult a physician. Material is corrosive.

Inhalation-

Remove to fresh air. If fumes are inhaled, call a physician.

Eyes-

Flush with water for at least 15 minutes to remove all residues. **GET MEDICAL HELP NOW! BLINDNESS CAN RESULT!**

6. PRECAUTIONS/PROCEDURES

Spills:

Contain spill, absorb, sweep up and dispose. Flush area to chemical sewer.

Waste Disposal Method:

Dispose of in accordance with all local, state and federal regulations.

Handling & Storage:

Store flux at ambient conditions. Wash thoroughly after handling to remove all residues.

Other Precautions:

Do not breathe fumes. Professionally wash contaminated clothing before reuse. Existing lung disorders will have increased toxic susceptibility.

Respiratory Protection:

If the workstation is not properly ventilated to exhaust all fumes and vapors, use a NIOSH approved mask.

Ventilation:

Maintain airflow away from user to remove all fumes and vapors, so that the PEL is never exceeded. Adhere to environmental regulations for exhausts.

Protective Gloves:

Chemical and acid impervious.

Eye Protection:

Chemical tight safety goggles. **DO NOT** wear contact lenses.

Other Protective Equipment:

Full protective equipment normally used in a soldering operation so as to prevent any contact.

7. REACTIVITY DATA

Stability: STABLE

Conditions to Avoid: NONE

Hazardous Polymerization: WILL NOT OCCUR

Incompatibility: STRONG NITRIC, SULFURIC ACID, CYANIDE

Hazardous Decomposition: HYDROCHLORIC/BROMIC ACID AND AMMONIA

8. TRANSPORTATION INFORMATION

Proper Shipping Name:	Corrosive Liquid, N.O.S. (Hydrobromic Acid)
Hazard Class:	Class 5
ID & Packing Group Number:	UN 1760, PG III
ERG Guide Number:	60

This Material Safety Data Sheet is offered for your information, consideration and investigation. ARGCO provides no warranties, either expressed or implied, and assumes no responsibilities for the accuracy or completeness of the data contained in this document. The data in this Material Safety Data Sheet relates to this product and does not relate to use in combination with any other material or in any process.