

HAZARD COMMUNICATION SAFETY DATA SHEET
TUF-CUT™ THREADING OIL- DARK

SECTION I – PRODUCT INFORMATION

Distributor's name: Allied Rubber & Gasket Company, Inc. - ARGCO
3145 Tiger Run Court #105
Carlsbad, CA 92010
For information call: (800) 854-1015
Date prepared: 2/16/2024
Product name: Tuf-Cut™ Dark Threading Oil
Recommended Use: Lubrication for threading and cutting pipe

SECTION II – HAZARDS IDENTIFICATION

Emergency Overview



SLIGHT IRRITANT
(SKIN AND EYE)



AVOID
STRONG OXIDIZERS

Routes of Entry: Inhalation, Skin, Ingestion

Health Hazard (acute & chronic): No known acute health hazards

2

Prolonged or frequent use may cause mild skin and eye irritation

Target organs (oil mist): Respiratory system & skin

Carcinogenicity: None known

Sign & Symptoms of Overexposure: Possible red and/or itching skin due to overexposure

Medical Conditions generally aggravated by Exposure: None known

Emergency & First Aid Procedures:

Eye Contact: Flush with water for at least 15 minutes and seek medical attention immediately.

Skin Contact: Wash with soap and water.

Inhalation: If a person breathes in large amounts of this product, move the exposed person to fresh air at once.

Incompatibility (material to avoid): Strong oxidizing agents

Hazardous Decomposition or Byproducts: CO, CO₂

SECTION III – COMPOSITION/INGREDIENTS

CAS #: None

Contains components listed with TSCA

Boiling Point: 760MM HG F, C Specific Gravity: (H₂O=1) 0.88

Vapor Pressure: (mm Hg @ 20C) ND Melting Point: N/A

Vapor Density: ND Evaporation Rate: (Butyl Acetate=1)>1

Solubility in Water: Negligible pH: ND/A

Appearance & Odor: Dark Oil/Characteristic Odor

SECTION VI – FIRST AID MEASURES

HMIS/NFPA Health – 0 Fire – 0 Reactivity – 0 Personal Protection - B

Steps to be taken in case material is released or

Spilled: Wipe up with paper towels or cloth and place in appropriate containers for disposal.

Material is non-hazardous waste.

Storage Temperature: Ambient

Handling: No special handling or storage procedures required.

Disposal Considerations: In accordance with federal, state, and local regulations.

SECTION V – FIRE FIGHTING MEASURES

Flash Point: >330F (COC)

Flammable Limits: LEL ND UEL ND

Extinguishing Media: Dry Chemical, Foam, CO₂

Special Fire Fighting Procedure: Fire fighters should wear self –contained breathing apparatus.

Unusual Fire & Explosion Hazards: None

SECTION VI – REACTIVITY DATA

Stability: Stable

Incompatibility (material to avoid): Strong oxidizing agents

Hazardous Decomposition or Byproducts: CO, CO₂

Hazardous Polymerization: Will not occur

Conditions to Avoid: None

SECTION VIII – SPECIAL PRECAUTIONS

Steps to be Taken in Case Material is Released or Spilled:

Extinguish all flames in area. Dike spill and soak up on inert absorbent material.

Waste Disposal Method:

Follow governmental and corporate regulations for lubricating oil.

Precautions to be Taken in Handling & Storage:

Store containers closed, away from extreme heat & open flames.

Other Precautions:

Use good personal hygiene. For industrial use only. Avoid breathing mist.

Eye Protection:

Safety glasses.

Other Protective Clothing:

None

Work/Hygienic Practices:

Launder soiled clothing before reuse. Keep work area neat. Clean up spills immediately. Practice good personal hygiene.

PLEASE NOTE: If you repackage or otherwise redistribute this product to industrial customers, a notice similar to this one should be sent to that customer.

SECTION IX - TRANSPORTATION INFORMATION

Product is not regulated.

Disclaimer

The information contained herein is accurate and reliable as of the date issued to the best of the manufacturer's knowledge. ARGCO doesn't warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising from the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

END OF SDS