

# HIGH DENSITY PINK PLUMBER'S TAPE

## [0.8 density]



### APPLICATION

For plumbers and pipe fitters.

Twice the density of standard white PTFE tape, making it easier to handle.

0.8 density tape makes it unnecessary to wrap so many revolutions around the pipe.

Color coded pink to signify that it is heavier than standard white thread seal tapes.

This specification applies to expanded, 0.8 density Pink PTFE Thread Seal Tape supplied on finished spools.

Ensures leak free joints.

Exceeds MIL Spec T-27730A.

### COMPOSITION

Min. 99% virgin PTFE, Max. 1% Pigment

### GENERAL APPEARANCE

The tape appears pale pink in color. It shall be free of visible voids, cracks, folds, contamination and have consistent physical properties.

### PACKAGING

The 0.8 density expanded PTFE Thread Seal Tapes are wound in 1 inch 1D plastic spools unless otherwise specified.

Bulk packaging is sufficient to prevent damage during shipment.

**USEFUL TEMPERATURE RANGE:** -450°F to +500°F

**REACTIVITY:** Chemically inert to virtually all environments

**FLAMMABILITY:** Non-Flammable

**STORAGE:** Unlimited shelf-life (Less than 70° recommended)

Capable of sealing all liquids and gases.

Oxygen is the only exception.

ARGCO offers special green color coded tape for oxygen (item # 60-10-150)

### ARGCO PART NUMBERS:

60-10-160: 1/2" x 260"

60-10-165: 3/4" x 260"

60-10-162: 1/2" x 520"

60-10-167: 3/4" x 520"

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	