

data sheet

ARGCO



PVC PIPE WRAP TAPE (10 MIL)



Features: This tape consists of stabilized, plasticized PVC film coated with a non-corrosion pressure-sensitive adhesive. Excellence in moisture resistant and anti-corrosive, outstanding conformability and adhesion to metal and plastic.

Physical Properties:

Total Thickness: 10 MIL (0.25mm)

Tensile Strength: 25 lbs./in (43.8 N/10mm)

Elongation at Break: 200%

Adhesion to Steel: 20 oz./in. (2.4 N/10mm)

Adhesion to Backing: 20 oz./in. (2.4 N/10mm)

Dielectric Strength: 1250 Volts/MIL

60-15-105: PVC Pipewrap 2" x 10 mil x 100'
60-15-110: PVC Pipewrap 6" x 10 mil x 100'
60-15-205T: PVC Pipewrap UPC printed 2" x 10 mil x 100'
60-15-208: PVC Pipewrap UPC printed 4" x 10 mil x 100'

The physical and performance properties shown are averages obtained from tests recommended by ASTM D-1000, or our own procedures. A particular roll may vary slightly from these averages and it is recommended that the buyer determine the suitability for his own purposes.

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015
OR LOG ONTO WWW.ARGCO.COM**