

# data sheet

## **ARGCO**



### **FIRE DEPARTMENT CONNECTIONS (GROOVE OUTLET)**

Groove Outlet Fire Department Connection is Underwriters' Laboratories listed and Factory Mutual Approved. Manufactured from solid brass components to increase service life, the single clapper design features a brass clapper and brass seats within a cast brass body.

- Pin lug swivels for ease of use and compatibility with local fire districts.
- Includes EPDM Swivel gaskets are included.
- Break caps should be installed to protect swivels and prevent debris from entering into the system.

#### **STRAIGHT PATTERN FDC BODIES**



#### **2-Way Straight Pattern Single Clapper**

**65-10-200-GRV:** 4" Groove outlet x 2-1/2"(F) x 2-1/2"(F) NST

Finish: rough brass

Branding: "AUTO-SPKR"



\*Contains lead. Not for use in water systems intended for human consumption.

#### **90° PATTERN FDC BODIES**



#### **2 Way 90 Degree Pattern Single Clapper**

**65-10-205-GRV:** 4" Groove outlet x 2-1/2"(F) x 2-1/2"(F) NST

Finish: rough brass

Branding: "AUTO-SPKR"

\*Contains lead. Not for use in water systems intended for human consumption.

#### **INSTALLATION:**

Prior to installation, make sure the proper identification sign has been installed on the outlet side of the FDC.

A "rigid style" mechanical coupling should be used.

Make sure the coupling gasket is properly lubricated with Tuf-Lube® Coupling Grease to insure proper seating of gasket to FDC mating surfaces.

Refer to coupling installation procedures for proper installation technique.

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015  
OR LOG ONTO WWW.ARGCO.COM**