

data sheet

ARGCO



THREADED ROD FASTENERS FOR CONCRETE



One piece self-tapping for use in concrete

ITEM #	MOUNT DIRECTION	ROD SIZE	SHANK DIA.	SHANK LENGTH	THREAD STYLE	PRE-DRILL DIAMETER
25-30-313V	BOTTOM	3/8"	1/4"	1-1/2"	ANSI Wedge-Bolt thread	3/8" ANSI



ULTIMATE LOAD CAPACITIES INSTALL IN NORMAL WEIGHT CONCRETE

ITEM #	ROD SIZE	EMBEDMENT DEPTH	MAX. CLAMPING TORQUE	2,000 PSI CONCRETE		4,000 PSI CONCRETE		6,000 PSI CONCRETE	
				TENSION LBS.	TENSION LBS.	TENSION LBS.	TENSION LBS.	TENSION LBS.	TENSION LBS.
25-30-313V	3/8"	1-1/2"	8 ft - lbs.	1,760	2,580	2,595	2,640	2,770	2,700

CROSS REFERENCE




ITEM #	ELCO	ITW SAMMY
	HANGERMATE®	SUPERSCREW®
25-30-313V	EZG-730*	CST-200

*Hangermate product features 5/16" shank

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015
OR LOG ONTO WWW.ARGCO.COM**

THREADED ROD FASTENERS FOR CONCRETE

ITEM #	MODEL	ROD SIZE	SHANK DIA.	SHANK LENGTH	LOAD CAPACITY	APPROVALS
25-30-313	SAMMY CST-20	3/8"-16	5/16"	1-1/2"	1,500	
25-30-313V	VERTIGO	3/8"-16	5/16"	1-1/2"	1,500	 
25-30-313B	SAMMY CST-200	1/4"-20	1/4"	1-1/2"	1,500	
25-30-313E	ELCO EZG-730	3/8"-16	5/16"	2-1/4"	1,500	
25-30-312	SAMMY CST-2	1/2"-13	5/16"	1-1/2"	1,500	