

FIRE HOSE

SINGLE JACKET



Single jacket fire hose is manufactured in accordance with National Fire Protection Association (NFPA) standard, current edition.

The polyester construction is mildew & rot-proof.

Single jacket fire hose is typically used for wash down, maintenance, mill discharge, and construction use due to it's 250 PSI service pressure rating.



- 100% high tenacity polyester jacket
- EPDM rubber lined
- 250 PSI service pressure - 500 PSI test pressure
- Standard color: White.
- Additional colors also available
- Standard coupling material: Brass
- Optional coupling material: Aluminum
- Standard coupling thread spec: NST (hose thread)
- Optional coupling thread spec: NPSH (pipe thread)
- Temperature rating: -58° F — 176° F

| Item # | DESCRIPTION |
|---------|---|
| 6510801 | Fire Hose 1-1/2" x 100' w/ Brass Couplings NST (UL) |
| 6510802 | Fire Hose 1-1/2" x 75' w/ Brass Couplings NST (UL) |
| 6510803 | Fire Hose 1-1/2" x 50' w/ Brass Couplings NST (UL) |

| | | | | | | | |
|--------------|--|----------|--|--------------|--|-----------|--|
| System No. | | Location | | Spec Section | | Paragraph | |
| Submitted By | | Date | | Approved | | Date | |