

ANTI-FREEZE
Propylene Glycol 38% Pre-Mix



Factory Pre-Mix
 Complies with NFPA guidelines

Blended with corrosion inhibitors
 Protects metal components and prolongs system life

Non-Toxic
 FDA Classification of Generally regarded
 as safe (G.R.A.S.) to humans & animals

Non-toxic, propylene glycol-based antifreeze for use in wet fire
 sprinkler systems, with the exception of CPVC and galvanized.
 Factory pre-mixed to NFPA guidelines of a 38% Propylene Glycol
 solution by volume. All fire sprinkler systems utilizing Propylene Glycol
 should conform to local, state and NFPA requirements.



Applications: Used in any environment where the potential exists for freezing conditions.
 When used undiluted, Propylene Glycol PreMix protects against freeze damage failure and ensure flow
 in wet fire sprinkler systems.

*NFPA 2016 7.6.2.1 and 7.6.2.2: Premixed Antifreeze Solution. A mixture of an antifreeze material with
 water that is prepared by the manufacturer at a factory with a quality control procedure in place that en-
 sures that the antifreeze solution remains homogeneous.

% of Propylene Glycol 38 Pre-Mix	Freeze Point	Flow Point	Burst Point	Specific Gravity @77°F
100	-0° F	-15° F	-50° F	103.7


INSTALLATION:

- Empty all water from system and drain sprinkler drops according to NFPA requirements.
- Propylene Glycol mix should be tested prior to introduction to system
- Do not dilute or add concentrate to Propylene Glycol 38% Pre Mix
- After filling system, follow NFPA guidelines for testing antifreeze.
- NFPA requires a tag to be affixed to the riser indicating the date tested or replaced, the type and concentration by volume of fluid used, system capacity, contractor name and license number, and a statement indicating if the entire system was drained and replaced with antifreeze.

Item number 1010226: 5 gallon pail Propylene Glycol 38% Pre-Mix
 Item number 1010225: 55 gallon drum Propylene Glycol 38% Pre-Mix

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	

FREEZING POINTS OF GLYCEROL-WATER SOLUTIONS



Lane, L. B., *Ind. Eng. Chem.*, 17, 924 (1925).

DENSITY OF ANTIFREEZE:

1 cubic foot of a Liquid (ft³ - cu ft) = 7.48052

Multiply the pounds per gallon of the selected antifreeze by 7.48

Propylene Glycol 38%

7.48 x 9.18 Lbs = 86.66 Lbs.

Lbs. per gallon:

5 gallon Pail: 42 Lbs.

8.478 lbs

55 gallon drum: 466 lbs

8.478 lbs

275 gallon tote: 2,332 lbs

8.478 lbs

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	