

data sheet

ARGCO



Tuf-Cut Threading Oil for CPVC

ARGCO

TUF-CUT Pipe threading oil is specially formulated for use with CPVC Piping Systems.

- Heavy Duty Cutting Oil
- Excellent Tool Life
- Chlorine Free
- All types of ferrous metal or pipe
- Improved Surface Finish
- FGG/BM/CZ™ System Compatible*

No Sulfur - No Humes.
Light mineral oil base provides better lubrication and heat dispersion characteristics and prevents binding and catching of dies.

Volatile Organic Compounds:
Minimal.
1.5% or less than 20 grams per liter.

For MSDS information contact ARGCO at 800-854-1015 or log onto argco.com

Made in USA

TUF-CUT CUTTING OIL FOR CPVC PIPE

FGG - BM - CZ
SYSTEM COMPATIBLE

1 GALLON

TUF-CUT for CPVC Pipe is recommended for threading and cutting operations whose chemical compatibility with FlowGuard Gold®, BlazeMaster®, and Corzan® pipe and fittings is a concern. TUF-CUT for CPVC Pipe also works excellent on most types of metal alloys that are difficult to machine.

DIRECTIONS FOR USE

1. Start the flow of oil before dies are in contact with the pipe.
2. Flood the area being cut or threaded to insure against occasional dry cutting periods. Failure to keep surface oiled can result in damage to cutting tools and grinding wheels.
3. Keep the flow of oil on the work zone until the operation of cutting or threading is complete.

*FGG/BM/CZ™ System Compatible means this product has been tested by Lubrizol Advanced Materials and is recommended for use on pipe and fittings made of FlowGuard Gold®, BlazeMaster®, and Corzan® pipe and fittings.



Tuf-Cut for CPVC is is specially formulated to assure chemical compatibility with FlowGuard Gold®, BlazeMaster®, and Corzan® pipe and fittings and has been added to the FGG/BM/CZ™ System Compatible Program.

Tuf-Cut for CPVC is also formulated to prevent chip welding and prolong tool and die life at high or low speeds by reducing frictional heat and tool wear, as well as power consumption.

It also improves surface finish and pushes away metal filings and chips, providing a smooth cut finish. Rust and corrosion protection of the metal is also provided.

It contains no chlorine, halogens, PCB's or heavy metals, and is perfectly safe for use on potable water lines.

- 10-10-036:** Tuf-Cut for CPVC 1 gallon
- 10-10-037:** Tuf-Cut for CPVC 5 gallon

VOC CONTENT

Volatile Organic Compounds:
Minimal.
1.5% or less than 20 grams per liter.

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015
OR LOG ONTO WWW.ARGCO.COM**

