

Tuf-Cut Dark™ Threading Oil



Tuf Cut Dark with 2% active sulphur

Sulphur added to prevent metal-to-metal contact, and reduce friction and heat build-up.

- Chlorine added as a catalyst to activate the release of sulphur at an even lower temperature.
- Better lubrication and heat dispersion characteristics prevent binding and catching of dies.

Premium quality metalworking fluid formulated as an all purpose medium and heavy duty metal removal oil. It is an ideal oil for use in the shop where a number of applications are present thus reducing the number of oils needed.

CONTENTS: Refined petroleum distillate, and blended with proprietary additives known to contain sulfur, chlorine, a lubricity additive and trace of silicone polymers.

Refer to MSDS for additional information.

Sizes:

- 1 quart (1010044)
- 1 gallon (1010043)
- 5 gallon (1010041)
- 55 gallon (1010040)

VOC CONTENT

Volatile Organic Compounds:
Minimal.
2.5% or less than 20 grams per liter.

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015
OR LOG ONTO WWW.ARGCO.COM**