

THREADING

SUPERTRONIC 2000 Portable Power Threader

Quick and effortless production of safe precision threaded joints to approved standards.

NPT
NPT

1/4" - 2"
1/4" - 1 1/4"



The perfect portable threader for use in the workshop, on the site, for maintenance and repair work by both tradesman and industry. This highly versatile tool is ideal for use without a vise, in any areas of limited access such as tight corners, close to walls or ceilings. High performance output from minimal energy consumption.

- 1 1/2" and 2" die heads fit directly into the machine on 2" set #7.1260
- Both heads are held by the tension ring to prevent them from falling out
- Small die heads (1/4" - 1 1/4") are held by using the ROFIX adapter
- Innovative technology – the ROFIX automatic locking device ensures that the die head is held firmly in place. No hand contact with moving parts – increased safety.

Motor

- Reliable 750 W universal motor, double insulated.
- High reduction gear box guarantees constant power from motor to threading heads, in either direction.
- Threading speed of 15 - 25 rpm, with 60 rpm high speed rapid reverse
- Simple safety switch

Gears

- High reduction gears with spur wheel teeth, 7 parallel gear shafts, each ball bearing mounted on both sides for optimum constant level power transmission
- Compact gear housing carefully angled to facilitate access when working in confined spaces (corners and shafts), off-set die head mounting for working close up to walls
- High quality cast aluminum housing with protective epoxy coating
- Completely dust tight. Service-free, sealed lubrication.
- All controls ergonomically positioned
- Carefully designed center of gravity makes threading easy in all positions and protects the motor from damp and dirt when machine is put down

32



SUPERTRONIC 2000 - Sets

Complete in plastic carrying case containing threader, adapter, pipe clamp, and die heads.

nominal	lbs.	No.
NPT 1/2" - 3/4" - 1" - 1 1/4"	28.00	7.1259
NPT 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2"	39.50	7.1260

Support Arm

Hardened teeth and jaws for superior grip in both drive directions.

Description	max. thread	lbs.	No.
Forged pipe clamp	2"	3.75	7.1280

ROFIX Adapter

For mounting small external octagon die heads.

Description	die heads	lbs.	No.
ROFIX Adapter with locking ring	1/4" - 1 1/4"	1.80	7.1271

