

GROOVED END OF RUN REDUCING ELBOW (ADACAP) MODEL 203A



Ductile iron 90° grooved-end elbow with base support, designed for installation at the bottom of a riser system. An anchor can be placed in conjunction with the base to support the weight of the pipe, coupling and fluid.

Pipe Material

- Carbon steel, Schedule 10, Schedule 40.

Maximum Working Pressure

- Up to 300 psi/20 bar

Function

- Joins carbon steel pipe grooved pipe to threaded.

CERTIFICATIONS/LISTINGS

Underwriters Laboratories,
Underwriters Laboratories Canada, Factory Mutual.

SPECIFICATIONS - MATERIAL

Housing Sections:

Ductile Iron conforming to
ASTM A 536, Grade 65-45-12.

Housing Coating:

Standard: Orange Enamel
Available: Hot Dipped
Galvanized

Item #	Nominal Size in/mm	NPT BSP	Max Working Pressure psi/Bar	C-E inches mm
7010260	1-1/4" x 1/2"	1/2"	300	2.40
	32 x 15	15	20	61
7010261	1-1/4" x 3/4"	3/4"	300	2.40
	32 x 20	20	20	61
7010262	1-1/4" x 1"	1"	300	2.40
	32 x 25	25	20	61
7010263	1-1/2" x 1/2"	1/2"	300	2.52
	40 x 15	15	20	64
7010264	1-1/2" x 3/4"	3/4"	300	2.52
	40 x 20	20	20	64
7010265	1-1/2" x 1"	1"	300	2.52
	40 x 25	25	20	64
7010266	2" x 1/2"	1/2"	300	2.76
	50 x 15	15	20	70
7010267	2" x 3/4"	3/4"	300	2.76
	50 x 20	20	20	70
7010268	2" x 1"	1"	300	2.76
	50 x 25	25	20	70
7010268A	2-1/2" x 3/4"	3/4"	300	2.99
	65 x 20	20	20	76
7010268B	2-1/2" x 1"	1"	300	2.99
	65 x 25	25	20	76
7010268C	3" x 1"	1"	300	
	50 x 25	25	20	

System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	