DUCTILE IRON THREADED PIPE FITTINGS

ARGCO's line of Ductile Iron Threaded Fittings conform to, comply with the following standards: Mechanical Properties of Ductile Iron in accordance with ASTM A536 (Grade 65-45-12)



Hardness: 131-222 BHN

Fittings are manufctured in accordance with ASME B16.3 and ASME B16.14 Threads NPT per ASME B1.20.1 AVAILABLE IN 1" - 2" FITTINGS ARE AIR TESTED HYDROSTATIC DESIGN TEST PRESSURE 500 PSI





90° Elbows



CLICK HERE TO PURCHASE CLICK HERE FOR GALVANIZED

45° Elbows



CLICK HERE TO PURCHASE CLICK HERE FOR GALVANIZED

90° Reducing Elbows



CLICK HERE TO PURCHASE CLICK HERE FOR GALVANIZED

Street Elbows



CLICK HERE TO PURCHASE CLICK HERE FOR GALVANIZED

Straight Tees



CLICK HERE TO PURCHASE CLICK HERE FOR GALVANIZED

Reducing Tees



CLICK HERE TO PURCHASE CLICK HERE FOR GALVANIZED

Straight Couplings



CLICK HERE TO PURCHASE CLICK HERE FOR GALVANIZED

Reducing Couplings



CLICK HERE TO PURCHASE CLICK HERE FOR GALVANIZED

System No.	Location	
Submitted By	Date	


Spec Section	Paragraph	
Approved	Date	



DUCTILE IRON THREADED PIPE FITTINGS

ARGCO's line of Ductile Iron Threaded Fittings conform to, comply with the following standards: Mechanical Properties of Ductile Iron in accordance with ASTM A536 (Grade 65-45-12)

Hardness: 131-222 BHN







Crosses



CLICK HERE TO PURCHASE

CLICK HERE FOR GALVANIZED

Plugs



CLICK HERE TO PURCHASE

CLICK HERE FOR GALVANIZED

Bushings



CLICK HERE TO PURCHASE

CLICK HERE FOR GALVANIZED

Caps



CLICK HERE TO PURCHASE

CLICK HERE FOR GALVANIZED

Floor Flange



CLICK HERE TO PURCHASE

CLICK HERE FOR GALVANIZED

System No.	Location	
Submitted By	Date	

Spec Section	Paragraph	
Approved	Date	

