

FLEX DRAIN KITS

STAINLESS STEEL FLEXIBLE HOSE



PERFECT FOR STAIRWELLS!

Stainless Steel Flexible Drain Hose kits for Riser Assemblies

Includes two 4" Long Threaded x Grooved Nipples,
Two Grooved Couplings
Flex Drain Groove x Groove Hose 1" x 31-½" Length
Overall Assembled Length: 39 (990 mm)

ITEM #	Hose Size	Riser Size
6532002	1" assembly	for 1" to 2" Risers
6532003	1-1/4" assembly	for 1-1/2" to 3" Risers
6532004	2" assembly	for 4" to 8" Risers

Flexible Hoses are manufactured with corrosion resistant AISI Grade 304 Stainless Steel corrugated high flexibility tube.
Rated at a Maximum Ambient Temperature of 150°F (66°C)

Standard Rigid Grooved Couplings:

- Ductile Iron construction
- Non-lead orange paint
- Standard Gasket: Pre-Lubricated Grade E EPDM (Type A)
- Conforms to ASTM A536
- UL listed, FM Approved

Black Steel Nipples:

- Schedule 40
- WOG 150 PSI 150 At 150° F
- Saturated Steam Pressure 300



System No.		Location		Spec Section		Paragraph	
Submitted By		Date		Approved		Date	